elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECBS25W02

IP65 CONDUIT-BOX JOINT Ø20 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit-box

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Description

Connector for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread, supplied with pre-assembled gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 25 mm - Length 55 mm - Thread length 14 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	25 ÷ 25 mm	**Suitable for built-in installation box**	No	**Suitable for junction box**	Yes
Suitable for cable box	Yes	**Suitable for expansion ring**	No	**For tube diameter**	25 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	55 mm	**thread length**	14 mm	**Tipologia**	sacchetto da 2 pezzi

Barcode

8033954878601
Unit
1 NR
0.05 [kg]

8059307210362
Cardboard
100 NR
0.39x0.295x0.21 [m]
5 [kg]

ELETTROCANALI s.p.a. | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.