elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECMS32W02

CONDUIT-CONDUIT IP65 D.32 PACK 2 UNITS

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Joint conduit - conduit

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Description

Coupling for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 32 mm - Length 100 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
UV resistant	Yes	**Quality of surface coating**	Uncoated	**Surface polished**	No
Surface brushed	No	**Suitable for nominal tube diameter**	32 mm	**Two-part**	No
With inspection opening and cover	No	**With lock function**	No	**Type of lock function**	Other
Material sealing	Rubber	**With outer thread**	No	**With inner thread**	No
Separable	No	**Eccentric**	No		

Technical Characteristics

length	100 mm	**Tipologia**	sacchetto da 2 pezzi

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8033954878496

Unit

1 NR

0.094 [kg]



8033954870605

Cardboard

50 NR

0.39x0.295x0.3 [m]

4.7 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.