elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

# ECCI16W02

## BEND INSPECTIONABLE 90° IP40 Ø16 mm - GREY pack 2 pcs

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > Inspectionable 90° bend

### Technical Symbols/Marks/Approvals

IP40 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

## Description

90° inspection bend for the connection between two pipes of the same diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 16 mm

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

### CLASS EC000936 - Bend for installation tubes

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Polyvinyl chloride (PVC) | **Halogen free** | No |
| **Surface protection** | Untreated | **Colour** | Grey | **Model** | Plug-in |
| **Diameter** | 16 mm | **Flexible** | No | **UV resistant** | Yes |
| **Quality of surface coating** | Uncoated | **Surface polished** | No | **Surface brushed** | No |
| **Compressive strength class according to EN 61386-1** | None | **Impact strength class according to EN 61386-1** | Medium (class 3 / 2 Joule) | **Suitable for nominal tube diameter** | 16 mm |
| **With sleeve** | Yes | **Two-part** | Yes | **With inspection opening and cover** | Yes |
| **Radius** | 14.2 mm | **Bend angle** | 90 ° | | |

## Technical Characteristics

| | |
|---|---|
| **Tipologia** | sacchetto da 2 pezzi |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8033954878380

**Unit**

1 NR

0.0275 [kg]

8059307210522

**Cardboard**

200 NR

0.39x0.295x0.3 [m]

5.5 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.