elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCI20W02

BEND INSPECTIONABLE 90° IP40 Ø20 mm - GREY pack 2 pcs

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > Inspectionable 90° bend

Technical Symbols/Marks/Approvals

IP40 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Description

90° inspection bend for the connection between two pipes of the same diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 20 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	20 mm	**Flexible**	No	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	20 mm
With sleeve	Yes	**Two-part**	Yes	**With inspection opening and cover**	Yes
Radius	16.6 mm	**Bend angle**	90 °		

Technical Characteristics

Tipologia	sacchetto da 2 pezzi

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8033954878397

Unit

1 NR

0.04 [kg]



8059307210539

Cardboard

150 NR

0.39x0.295x0.21 [m]

6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.