elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC63236FPL

FLUSH-MOUNT BOX FOR 36M (2x18) ENCLOSURE - HOLLOW-WALLS

Enclosures > Recessed > Recessed modular enclosures > Series 632 essenza - modular enclosures > Small distribution board > Recessed dry-lining box

Technical Symbols/Marks/Approvals

IP40 | GWT 850° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Recessed base for lightweight walls - plasterboard or wood. Made of impact-resistant, low-smoke technopolymer. Resistance to abnormal heat up to 850°C (GWT). The base is secured to the structure with fins. Manufactured in compliance with EN 60670-1:2005, EN 60670-22:2013. Installation temperatures: minimum -15°C, maximum +60°C.
Dimensions: 297x520 mm
Depth: 85 mm
36 DIN modules (3x12)

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Hollow wall	**Width in number of modular spacings**	36	**Built-in depth**	85 mm
Colour	Blue	**Width**	297 mm	**Height**	520 mm
Depth	85 mm	**Built-in width**	297 mm	**Built-in height**	85 mm
RAL-number	5005	**UV resistant**	No	**Transparent cover/door**	No
With lock	No	**Inner depth**	81 mm	**Number of rows**	3
Extension possible	No	**Housing material**	Plastic	**With mounting plate**	No
Signal passing door	No	**Type of closure**	Other	**Earthing terminal block**	No
Neutral terminal block	No	**DIN-rail**	No	**EMC-version**	No

Technical Characteristics

dimensions	297x520x85 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Instruction booklet

Istruzioni 630-635_0125_0125.pdf

Dimensions and technical drawings

EC63236_FONDO_PL_2025.pdf

Barcode

8055035965871

Unit

1 NR

0.982 [kg]

8055035965932

Cardboard

2 NR

0.245x0.59x0.18 [m]

1.964 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.