

# EC63004CE

## FLUSH MOUNT.MOD.ENCLOSURE IP40 DIM.154X160X80 4 MOD. W.S.D. (1X4 T.B.)

Enclosures > Recessed > Recessed modular enclosures > Series 630 - masonry modular enclosures > Small distribution board > White - blank door - equipped

### Technical Symbols/Marks/Approvals

IP40 | GWT 650° | RoHS II | MADE IN ITALY

### Norms

EN 60670-1 EN 60670-24

## Description

Flush-mounting distribution board for masonry walls. Base made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 650°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Halogen-free ABS technopolymer door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 154x160 mm
Base depth 80 mm
4 DIN modules
2 terminal blocks 6x10 mm - 4 holes
Dissipated power 9 W



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Etim

### GROUP EG000023 - Distribution boards


### CLASS EC000214 - Small distribution board

| | | | | | |
|---|---|---|---|---|---|
| **Mounting method** | Flush-mounted | **Degree of protection (IP)** | IP40 | **Width in number of modular spacings** | 4 |
| **Built-in depth** | 80 mm | **Colour** | White | **Width** | 154 mm |
| **Height** | 160 mm | **Depth** | 97 mm | **Built-in width** | 144 mm |
| **Built-in height** | 80 mm | **RAL-number** | 9001 | **UV resistant** | No |
| **Type of covering** | Door | **Cover model** | With notch | **Type of door** | Single |
| **Transparent cover/door** | No | **With lock** | No | **Inner depth** | 80 mm |
| **Number of rows** | 1 | **Extension possible** | No | **Housing material** | Plastic |
| **With mounting plate** | No | **Signal passing door** | No | **Type of closure** | Other |
| **Earthing terminal block** | Yes | **Neutral terminal block** | Yes | **DIN-rail** | Yes |
| **EMC-version** | No | | | | |

## Technical Characteristics

| | | | | | |
|---|---|---|---|---|---|
| **dimensions** | 154x160x80 mm | **Mounting equipment** | 1 | **Terminal blocks/holes** | 2x4 |
| **Power dissipation** | 9 W | **Tipo_Morsettiera** | 4x16 mm² | | |

## Documentation available for download



**Instruction booklet**

Istruzioni 630-635_0125_0125.pdf



**Certification**

Serie 630 IMQ_CA02.01745_2026.pdf

## Dimensions and technical drawings

EC63004_2025.pdf



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8053676572342

**Unit**

1 NR

0.531 [kg]



8059307214476

**Cardboard**

20 NR

10.62 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.