

## EC63018NE

### FLUSH MOUNT.MOD.ENCLOSURE IP40 DIM.430X260X80 18 MOD. BLACK (1X12 T.B.)



IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

Enclosures > Recessed > Recessed modular enclosures >  
Series 630 - masonry modular enclosures > Small distribution  
board > Black -transparent door - equipped

#### Technical Symbols/Marks/Approvals



#### Norms

EN 60670-1 EN 60670-24

## Etim

### GROUP EG000023 - Distribution boards

### CLASS EC000214 - Small distribution board

|                               |               |                                  |        |                                            |         |
|-------------------------------|---------------|----------------------------------|--------|--------------------------------------------|---------|
| <b>Mounting method</b>        | Flush-mounted | <b>Degree of protection (IP)</b> | IP40   | <b>Width in number of modular spacings</b> | 18      |
| <b>Built-in depth</b>         | 80 mm         | <b>Colour</b>                    | Black  | <b>Width</b>                               | 430 mm  |
| <b>Height</b>                 | 260 mm        | <b>Depth</b>                     | 100 mm | <b>Built-in height</b>                     | 80 mm   |
| <b>RAL-number</b>             | 7021          | <b>Type of covering</b>          | Door   | <b>Type of door</b>                        | Single  |
| <b>Transparent cover/door</b> | Yes           | <b>With lock</b>                 | No     | <b>Inner depth</b>                         | 80 mm   |
| <b>Number of rows</b>         | 1             | <b>Extension possible</b>        | No     | <b>Housing material</b>                    | Plastic |
| <b>With mounting plate</b>    | No            | <b>Type of closure</b>           | Other  | <b>Earthing terminal block</b>             | Yes     |
| <b>Neutral terminal block</b> | Yes           | <b>DIN-rail</b>                  | Yes    | <b>EMC-version</b>                         | No      |

## Technical Characteristics

|                                              |               |                           |   |                              |      |
|----------------------------------------------|---------------|---------------------------|---|------------------------------|------|
| <b>dimensions</b>                            | 430x260x80 mm | <b>Mounting equipment</b> | 1 | <b>Terminal blocks/holes</b> | 2x12 |
| <b>Power dissipation (watts) EN 60670-24</b> | 30            |                           |   |                              |      |

## Documentation available for download

### Instruction booklet



Istruzioni 630-  
635\_0125\_0125.pdf

### Certification



Serie 630  
IMQ\_CA02.01745\_  
2020.pdf

## Barcode



8053676578436

### Unit

1 NR

1.765 [kg]