

EC63024E



FLUSH MOUNT.MOD.ENCLOSURE IP40 DIM.320X388X80 24 MOD. GREY (4X12 T.B.)



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Enclosures > Recessed > Recessed modular enclosures >
Series 630 - masonry modular enclosures > Small distribution
board > Grey -transparent door - equipped

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted	Degree of protection (IP)	IP40	Width in number of modular spacings	24
Built-in depth	80 mm	Colour	Grey	Width	320 mm
Height	388 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	7035	Type of covering	Door	Type of door	Single
Transparent cover/door	Yes	With lock	No	Inner depth	80 mm
Number of rows	2	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	Earthing terminal block	Yes
Neutral terminal block	Yes	DIN-rail	Yes	EMC-version	No

Technical Characteristics

dimensions	320x388x80 mm	Mounting equipment	1	Terminal blocks/holes	4x12
Power dissipation	35 W	Tipo_Morsettiera	2x16 + 10x10 mm ²		

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Certification



Serie 630
IMQ_CA02.01745_
2020.pdf

Dimensions and technical drawings



EC63024_2025.pdf

Barcode



8053676572441

Unit

1 NR

2.052 [kg]