

EC63024N



**FLUSH MOUNT.MOD.ENCLOSURE IP40
DIM. 320X388X80 24 MOD. BLACK**



Enclosures > Recessed > Recessed modular enclosures > Series 630 - masonry modular enclosures > Small distribution board > Black -transparent door

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

**GROUP EG000023 - Distribution boards
CLASS EC000214 - Small distribution board**


Mounting method	Flush-mounted	Degree of protection (IP)	IP40	Width in number of modular spacings	24
Built-in depth	80 mm	Colour	Black	Width	320 mm
Height	388 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	7021	Type of covering	Door	Type of door	Single
Transparent cover/door	Yes	With lock	No	Inner depth	80 mm
Number of rows	2	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	Earthing terminal block	No
Neutral terminal block	No	DIN-rail	Yes	EMC-version	No

Technical Characteristics

dimensions	320x388x80 mm	Power dissipation	35 W
-------------------	---------------	--------------------------	------

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Certification



Serie 630
IMQ_CA02.01745_
2020.pdf

Dimensions and technical drawings



EC63024_2025.pdf

Barcode



8032636763334

Unit

1 NR

0.33x0.41x0.16 [m]

1.954 [kg]