

EC63036C



**FLUSH-MOUNT MOD. ENCL. IP40
430X410X80 mm 36 MOD. WHITE
SOLID DOOR**



Enclosures > Recessed > Recessed modular enclosures > Series 630 - masonry modular enclosures > Small distribution board > White - blank door

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted	Degree of protection (IP)	IP40	Width in number of modular spacings	36
Built-in depth	80 mm	Colour	White	Width	430 mm
Height	410 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	9001	Type of covering	Door	Type of door	Single
Transparent cover/door	No	With lock	No	Inner depth	80 mm
Number of rows	2	Extension possible	No	Housing material	Plastic
With mounting plate	No	Type of closure	Other	Earthing terminal block	No
Neutral terminal block	No	DIN-rail	Yes	EMC-version	No

Technical Characteristics

dimensions	430x410x80 mm	Power dissipation	52 W
-------------------	---------------	--------------------------	------

Documentation available for download

Instruction booklet



Istruzioni 630-635_0125_0125.pdf

Certification



Serie 630
IMQ_CA02.01745_2020.pdf

Dimensions and technical drawings

EC63036_COPERCHIO_2025.pdf



EC63036_FONDO_2025.pdf

Barcode



8032793873112

Unit

1 NR

2.717 [kg]