

EC63124

FLUSH-MOUNT MODULAR ENCLOSURE IP40 24 MOD. METAL DOOR WHITE RAL9003

Enclosures > Recessed > Recessed modular enclosures > Series 631-636 - metal door modular enclosures > Small distribution board > Masonry enclosures

Technical Symbols/Marks/Approvals

UV | IP40 | GWT 650° | RoHS II | MADE IN BIH

Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for masonry walls. Base made of high-impact technopolymer with low smoke emission. Equipped with a spirit level for perfect horizontal alignment. Extra-flat design: constant wall protrusion of only 9 mm. Lockable internal door for DIN modules. Resistance to abnormal heat up to 650°C (GWT). Painted metal cover. Reversible cover. Painted metal door. Concealed central opening system. Option to install a cylinder safety lock. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 368x443x93 mm
Flush-mounting depth 314x414x86.5 mm
24+4 DIN modules (2x12)
2 terminal blocks 2x25+14x16
Dissipated power 80 W

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000023 - Distribution boards


CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	28
Built-in depth	84 mm	**Colour**	White	**Width**	368 mm
Height	443 mm	**Depth**	93 mm	**Built-in width**	314 mm
Built-in height	84 mm	**RAL-number**	9003	**UV resistant**	Yes
Type of covering	Door	**Cover model**	With notch	**Type of door**	Single
Transparent cover/door	No	**With lock**	No	**Inner depth**	84 mm
Number of rows	2	**Extension possible**	No	**Housing material**	Plastic
With mounting plate	No	**Signal passing door**	No	**Type of closure**	Push button
Earthing terminal block	Yes	**Neutral terminal block**	Yes	**DIN-rail**	Yes
EMC-version	No				

Technical Characteristics

dimensions	368x443x93 mm	**Terminal blocks/holes**	2x16	**Power dissipation**	80 W
Tipo_Morsettiera	2x25 + 14x16 mm²				

Documentation available for download



Instruction booklet

Serie 636 metallo.pdf

Barcode

8056351666848

Unit

1 NR

0.385x0.455x0.135 [m]

3.16 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.