

EC63524BE



DRY LINING MODULAR ENCLOSURE 24 MOD. - TRANSP. DOOR - RAL9001 (2X12 T.B.)



Enclosures > Recessed > Recessed modular enclosures >
Series 635 - dry lining modular enclosures > Small distribution
board > White -transparent door - equipped

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Flush-mounted/hollow wall	Degree of protection (IP)	IP40	Width in number of modular spacings	24
Built-in depth	80 mm	Colour	White	Width	320 mm
Height	388 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	9001	Type of door	Single	Transparent cover/door	Yes
With lock	No	Inner depth	80 mm	Number of rows	2
Extension possible	No	Housing material	Plastic	With mounting plate	No
Type of closure	Other	Earthing terminal block	Yes	Neutral terminal block	Yes
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

dimensions	320x388x80 mm	Mounting equipment	1	Terminal blocks/holes	4x12
Power dissipation (watts) EN 60670-24	35				

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf
f

Dimensions and technical drawings



EC63524_2025.pdf

Barcode



8053676572830

Unit

1 NR

2.252 [kg]