



EC63554BE

DRY LINING MODULAR ENCLOSURE 54 MOD. - TRANSP. DOOR - RAL9001 (4X12 T.B.)



Enclosures > Recessed > Recessed modular enclosures >
Series 635 - dry lining modular enclosures > Small distribution
board > White -transparent door - equipped

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board


Mounting method	Flush-mounted/hollow wall	Degree of protection (IP)	IP40	Width in number of modular spacings	54
Built-in depth	80 mm	Colour	White	Width	430 mm
Height	618 mm	Depth	100 mm	Built-in height	80 mm
RAL-number	9001	Type of door	Single	Transparent cover/door	Yes
With lock	No	Inner depth	80 mm	Number of rows	3
Extension possible	No	Housing material	Plastic	With mounting plate	No
Type of closure	Other	Earthing terminal block	Yes	Neutral terminal block	Yes
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

dimensions	430x618x80 mm	Mounting equipment	2	Terminal blocks/holes	8x12
Power dissipation (watts) EN 60670-24	77				

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings

EC63554_COPERCHIO_2025.pdf



EC63554_FONDO_2025.pdf

Barcode



8054382041948

Unit

1 NR

4.39 [kg]