



EC63572BE

DRY LINING MODULAR ENCLOSURE 72 MOD. - TRANSP. DOOR - RAL9001 (4X12 T.B.)



Enclosures > Recessed > Recessed modular enclosures >
Series 635 - dry lining modular enclosures > Small distribution
board > White -transparent door - equipped

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted/hollow wall	Degree of protection (IP)	IP40	Width in number of modular spacings	72
Built-in depth	95 mm	Colour	White	Width	450 mm
Height	853 mm	Depth	119 mm	Built-in height	95 mm
RAL-number	9001	Type of door	Double	Transparent cover/door	Yes
With lock	No	Inner depth	95 mm	Number of rows	4
Extension possible	No	Housing material	Plastic	With mounting plate	No
Type of closure	Other	Earthing terminal block	Yes	Neutral terminal block	Yes
DIN-rail	Yes	EMC-version	No		

Technical Characteristics

dimensions	450x853x95 mm	Mounting equipment	2	Terminal blocks/holes	8x12
Power dissipation (watts) EN 60670-24	90				

Documentation available for download

Instruction booklet



Istruzioni 630-
635_0125_0125.pdf

Dimensions and technical drawings

EC63572_COPERCHIO_2025.pdf



EC63572_FONDO_2025.pdf

Barcode



8054382041962

Unit

1 NR

6.89 [kg]