

**EC660322EI**

**SAFETY SWITCHES 32A - 2P - 78X85X88**

Industrial > Safety rotary switches > Safety switches > Panel-mount > Switch disconnector (low voltage) > Emergency red knob



**Technical Symbols/Marks/Approvals**



**Norms**

IEC947-3 EN60947-3 UL508

**Etim**

**GROUP EG000017 - Low-voltage switchgear and control gear**

**CLASS EC000216 - Switch disconnector (low voltage)**

Number of poles	2	Width	74 mm	Height	85 mm
Depth	88 mm	Version as main switch	No	Version as maintenance-/service switch	No
Version as safety switch	Yes	Version as emergency stop installation	No	Version as reversing switch	No
Number of switches	1	Max. rated operation voltage Ue AC	690 V	Rated operating voltage	230-690 V
Rated permanent current Iu	32 A	Rated permanent current at AC-23, 400 V	32 A	Rated permanent current at AC-21, 400 V	32 A
Rated operation power at AC-3, 400 V	15 kW	Rated short-time withstand current Icw	400 A	Rated operation power at AC-23, 400 V	18.5 kW
Switching power at 400 V	18.5 kW	Conditioned rated short-circuit current Iq	10 kA	Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0	Number of auxiliary contacts as change-over contact	0	Motor drive optional	No
Motor drive integrated	No	Voltage release optional	No	Device construction	Complete device in housing
Suitable for floor mounting	No	Suitable for front mounting 4-hole	No	Suitable for front mounting centre	No
Suitable for distribution board installation	Yes	Suitable for intermediate mounting	No	Colour control element	Red
Type of control element	Turn button	Interlockable	Yes	Type of electrical connection of main circuit	Cable clamp
With pre-assembled cabling	No	Degree of protection (IP), front side	IP65		

## Technical Characteristics

dimensions 74x85 mm

## Barcode



8054382042228

**Unit**

1 NR

0.13x0.13x0.075 [m]

0.2975 [kg]



8059307215114

**Cardboard**

12 NR

0.325x0.515x0.15 [m]

3.57 [kg]