
EC680M3

BRASS TERMINAL BLOCKS 12 HOLES

Enclosures > Accessories > Accessories > Terminal blocks > Terminals > Brass terminal blocks



Technical Symbols/Marks/Approvals

CE RoHS II MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Single-pole brass terminal block with 12 holes. Material used: UNI EN 12167 CW 614N brass. Rated voltage 400VAC. Rated current 100A. Supplied complete with corrosion-resistant treated steel screws with combined or screwdriver slot.
Section 6x10 mm - Length 82.5 mm.
2 holes x 16 mm² - 10 holes x 10 mm².

Etim

GROUP EG000015 - Energy distribution systems

CLASS EC000275 - Main line branch terminal

Number of poles	1	**Mounting method**	Screw	**Width**	82.5 mm
Height	10 mm	**Depth**	6 mm	**Connection type**	Screwing
Nominal current	100 A	**Number of inputs**	2	**Number of outputs**	10
Suitable for solid conductors	Yes	**Suitable for stranded conductors**	Yes	**Suitable for fine strand conductors**	No
Suitable for fine strand conductors without cable end sleeve	No	**Suitable for extra fine-strand conductors**	No	**Suitable for extra fine-strand conductors without cable end sleeve**	No
Conductor cross section, input	16 ÷ 16 mm²	**Conductor cross section, output**	10 ÷ 10 mm²	**Contact safe**	No

Dimensions and technical drawings

EC680M3.2026.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880882830

Cardboard

10 NR

0.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.