elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

EC680M6

BRASS TERMINAL BLOCKS 10 HOLES

Enclosures > Accessories > Accessories > Terminal blocks > Terminals > Brass terminal blocks



Technical Symbols/Marks/Approvals

CE | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Single-pole brass terminal block with 10 holes. Material used: UNI EN 12167 CW 614N brass. Rated voltage 400VAC. Rated current 125A. Supplied complete with corrosion-resistant treated steel screws with combined or screwdriver slot.
Section 10x15 mm - Length 88 mm.
2 holes x 25 mm² - 8 holes x 10 mm².

Etim

GROUP EG000015 - Energy distribution systems

CLASS EC000275 - Main line branch terminal

Number of poles	1	**Mounting method**	Screw	**Width**	88 mm
Height	15 mm	**Depth**	10 mm	**Connection type**	Screwing
Nominal current	100 A	**Number of inputs**	2	**Number of outputs**	8
Suitable for solid conductors	Yes	**Suitable for stranded conductors**	Yes	**Suitable for fine strand conductors**	No
Suitable for fine strand conductors without cable end sleeve	No	**Suitable for extra fine-strand conductors**	No	**Suitable for extra fine-strand conductors without cable end sleeve**	No
Conductor cross section, input	25 ÷ 25 mm²	**Conductor cross section, output**	10 ÷ 10 mm²	**Contact safe**	No

Dimensions and technical drawings

EC680M6.2026.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880882861

Cardboard

10 NR

0.9 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.