

EC6900715



BOARD FOR CONSTRUCTION SITE ASC 4 SOCKETS IOSBF - TERMINAL BLOCKS



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Industrial > Distribution boards > Distribution boards > Series
acs - panel system 700 > Energy distributor for construction
site > 4 horizontal interlocked sockets - power supply with
terminal block

Technical Symbols/Marks/Approvals



Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000023 - Distribution boards

CLASS EC000484 - Energy distributor for construction site

| | | | | | |
|--|---------------------|--|---------|--|--------|
| Rated current | 16 A | Leakage current type | Other | Degree of protection (IP) | IP65 |
| Width | 677 mm | Height | 658 mm | Depth | 288 mm |
| Model | Distributor cabinet | Housing material | Plastic | Number of socket outlets with protective contact CEE 7/3 (type F) | 0 |
| Number of socket outlets Swiss standard type 13 | 0 | Number of socket outlets Swiss standard type 15 | 0 | Number of socket outlets Swiss standard type 23 | 0 |
| Number of socket outlets Swiss standard type 25 | 0 | Number of miniature circuit breakers (MCB) | 1 | Rated voltage | 230 V |
| Connected load | 3.6 kW | Number of CEE socket outlets (IEC 60309) 16 A / 24 V / 2P (L, N) | 0 | Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 3P (L, N, PE) | 4 |
| Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 5P (1, 2, 3, N, PE) | 0 | Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 4P (1, 2, 3, PE) | 0 | Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE) | 0 |
| Number of CEE socket outlets (IEC 60309) 32 A / 230 V / 4P (1, 2, 3, PE) | 0 | Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 4P (1, 2, 3, PE) | 0 | Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE) | 0 |
| Number of CEE socket outlets (IEC 60309) 63 A / 230 V / 4P (1, 2, 3, PE) | 0 | Number of CEE socket outlets (IEC 60309) 63 A / 400 V / 5P (1, 2, 3, N, PE) | 0 | Number of CEE socket outlets (IEC 60309) 125 A / 230 V / 4P (1, 2, 3, PE) | 0 |
| Number of CEE socket outlets (IEC 60309) 125A / 400 V / 5P (1, 2, 3, N, PE) | 0 | Number of meter panels | 0 | Main switch | Other |
| Main switch rated current | 16 A | Number of poles main switch | 2 | Number of earth leakage switches 10 mA | 0 |
| Number of earth leakage switches 30 mA | 1 | Number of earth leakage switches 100 mA | 0 | Number of earth leakage switches 300 mA | 0 |
| Emergency stop button | Yes | Suitable according to IEC/EN 61439-4 | Yes | | |

Technical Characteristics

| | | | | | |
|-----------------------|---|---------------------------------|--------|---------------------------------|---|
| Prese_16A_2P+T | 4 | Prese_32A_2P+T | - | Prese_16A_3P+N+T | - |
| Prese_16A_3P+T | - | outlet protection mt 16A | 1x1P+N | outlet protection mt 32A | - |
| prese_32A_3P+T | - | Prese_32A_3P+N+T | - | | |

Documentation available for download

Electical diagram
6900715.pdf



Barcode



8056351662246

Unit

1 NR

25 [kg]