

EC6900723



**BOARD FOR CONSTRUCTION SITE
ASC 5 SOCKETS IOSBF - TERMINAL
BLOCKS**



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Industrial > Distribution boards > Distribution boards > Series
acs - panel system 700 > Energy distributor for construction
site > 5 horizontal interlocked sockets - power supply with
terminal block

Technical Symbols/Marks/Approvals

IP65

GWT
650°



CE

RoHS II



MADE
IN
ITALY

Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000023 - Distribution boards


CLASS EC000484 - Energy distributor for construction site

Rated current	32 A	Leakage current type	Other	Degree of protection (IP)	IP65
Width	677 mm	Height	658 mm	Depth	288 mm
Model	Distributor cabinet	Housing material	Plastic	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Number of miniature circuit breakers (MCB)	1	Rated voltage	400 V
Connected load	21 kW	Number of CEE socket outlets (IEC 60309) 16 A / 24 V / 2P (L, N)	0	Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 3P (L, N, PE)	3
Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 5P (1, 2, 3, N, PE)	0	Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 4P (1, 2, 3, PE)	1	Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE)	0
Number of CEE socket outlets (IEC 60309) 32 A / 230 V / 4P (1, 2, 3, PE)	0	Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 4P (1, 2, 3, PE)	1	Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE)	0
Number of CEE socket outlets (IEC 60309) 63 A / 230 V / 4P (1, 2, 3, PE)	0	Number of CEE socket outlets (IEC 60309) 63 A / 400 V / 5P (1, 2, 3, N, PE)	0	Number of CEE socket outlets (IEC 60309) 125 A / 230 V / 4P (1, 2, 3, PE)	0
Number of CEE socket outlets (IEC 60309) 125A / 400 V / 5P (1, 2, 3, N, PE)	0	Number of meter panels	0	Main switch	Other
Main switch rated current	32 A	Number of poles main switch	4	Number of earth leakage switches 10 mA	0
Number of earth leakage switches 30 mA	1	Number of earth leakage switches 100 mA	0	Number of earth leakage switches 300 mA	0
Emergency stop button	Yes	Suitable according to IEC/EN 61439-4	Yes		

Technical Characteristics

Prese_16A_2P+T	3	Prese_32A_2P+T	-	Prese_16A_3P+N+T	-
Prese_16A_3P+T	1	outlet protection mt 16A	1x4P	outlet protection mt 32A	-
prese_32A_3P+T	1	Prese_32A_3P+N+T	-		

Documentation available for download



Barcode



8056351662291

Unit

1 NR

26 [kg]