

EC6900847



**DISTR. BOARD FOR CONSTRUCTION
SITE 3X2P16-1X3P16-1X3P+N16-
1X3P32**



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Industrial > Distribution boards > Distribution boards > Series
acs - panel system 800 > Energy distributor for construction
site > 6 horizontal interlocked sockets - power supply with
terminal block

Technical Symbols/Marks/Approvals

IP65

GWT
650°



CE

RoHS II



MADE
IN
ITALY

Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000023 - Distribution boards

CLASS EC000484 - Energy distributor for construction site


| | | | | | |
|---|---------------------|--|---------|--|--------|
| Rated current | 63 A | Leakage current type | Other | Degree of protection (IP) | IP65 |
| Width | 870 mm | Height | 720 mm | Depth | 375 mm |
| Model | Distributor cabinet | Housing material | Plastic | Number of socket outlets with protective contact CEE 7/3 (type F) | 0 |
| Number of socket outlets Swiss standard type 13 | 0 | Number of socket outlets Swiss standard type 15 | 0 | Number of socket outlets Swiss standard type 23 | 0 |
| Number of socket outlets Swiss standard type 25 | 0 | Number of miniature circuit breakers (MCB) | 3 | Rated voltage | 400 V |
| Connected load | 35 kW | Number of CEE socket outlets (IEC 60309) 16 A / 24 V / 2P (L, N) | 0 | Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 3P (L, N, PE) | 3 |
| Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 5P (1, 2, 3, N, PE) | 0 | Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 4P (1, 2, 3, PE) | 1 | Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE) | 1 |
| Number of CEE socket outlets (IEC 60309) 32 A / 230 V / 4P (1, 2, 3, PE) | 0 | Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 4P (1, 2, 3, PE) | 1 | Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE) | 0 |
| Number of CEE socket outlets (IEC 60309) 63 A / 230 V / 4P (1, 2, 3, PE) | 0 | Number of CEE socket outlets (IEC 60309) 63 A / 400 V / 5P (1, 2, 3, N, PE) | 0 | Number of CEE socket outlets (IEC 60309) 125 A / 230 V / 4P (1, 2, 3, PE) | 0 |
| Number of CEE socket outlets (IEC 60309) 125 A / 400 V / 5P (1, 2, 3, N, PE) | 0 | Number of meter panels | 0 | Main switch | Other |
| Main switch rated current | 63 A | Number of poles main switch | 4 | Number of earth leakage switches 10 mA | 0 |
| Number of earth leakage switches 30 mA | 1 | Number of earth leakage switches 100 mA | 0 | Number of earth leakage switches 300 mA | 0 |
| Emergency stop button | Yes | Suitable according to IEC/EN 61439-4 | Yes | | |

Technical Characteristics

| | | | | | |
|---------------------------------|-------------|---------------------------------|------|--------------------------------|---|
| Differential device | combinato | Prese_16A_2P+T | 3 | Prese_32A_2P+T | - |
| Prese_16A_3P+N+T | 1 | Prese_16A_3P+T | 1 | Schuko/bivalent sockets | - |
| outlet protection mt 16A | 1x2P - 1x4P | outlet protection mt 32A | 1x3P | shuko bivalent 16A 2P+E | - |
| prese_32A_3P+T | 1 | Prese_32A_3P+N+T | - | | |


Documentation available for download

Instruction booklet



GUIDA DI RIFERIMENTO QUADRI DA CANTIERE TIPO 69008.pdf

Electical diagram



6900847.pdf

Barcode



8033954872777

Unit

1 NR

1.025x0.395x0.74 [m]

34 [kg]