

EC69021

FLANGED BOARD FOR 2 SOCKETS - 4 MOD.

Industrial > Distribution boards > Distribution boards > Unwired versions > Small distribution board > 2 sockets - 4 modules

Technical Symbols/Marks/Approvals

IP65 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Distribution board for modular devices and industrial sockets. Made of shock-resistant ABS-based technopolymer. Galvanized steel DIN rail mounted on the bottom and depth-adjustable. Knockouts for pipe or cable entry with grommets, conduit fittings or cable glands of various sizes. Supplied as standard with screw caps for double insulation. Door closure with triangular key included. Blank flanges included. Manufactured in compliance with EN 60670-1 and EN 60670-24 standards.
Flanged model for 2 x 16A sockets with 75x85 mm flange and 60x60 mm fixing centers. Dimensions 105x337x95 mm. 4 DIN modules. Dissipable power 9 W.

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	**Degree of protection (IP)**	IP65	**Width in number of modular spacings**	4
Colour	Grey	**Width**	105 mm	**Height**	337 mm
Depth	95 mm	**Built-in width**	98 mm	**RAL-number**	7035
UV resistant	Yes	**Type of covering**	Lid	**Cover model**	With notch
Type of door	Single	**Transparent cover/door**	Yes	**With lock**	Yes
Inner depth	68 mm	**Number of rows**	1	**Extension possible**	Yes
Housing material	Plastic	**With mounting plate**	No	**Signal passing door**	No
Type of closure	Three-square	**Earthing terminal block**	No	**Neutral terminal block**	No
DIN-rail	Yes	**EMC-version**	No		

Technical Characteristics

Power dissipation	9 W	**Prese_32A_2P+T**	-	**Prese_16A_3P+N+T**	-

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Instruction booklet

Istruzioni 690_0423.pdf



Instruction booklet

Sinottico 690_1.pdf



Instruction booklet

Sinottico 690_2.pdf



Certification

Serie 690-IMQ_CA02.03487_2018.pdf

Dimensions and technical drawings

EC69021_2025.pdf

Barcode

8032793874317

Unit

1 NR

0.105x0.435x0.095 [m]

0.7 [kg]

8059307215633

Cardboard

15 NR

0.415x0.6x0.44 [m]

10.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.