

EC6902100

ASSEMBLED DISTR. BOARD ASC TYPE 2 VERT. SOCKETS IP44 1X2P+E -1X3P+E

Industrial > Distribution boards > Distribution boards > Series asc - board system > Cee socket outlet combination (iec 60309) > 2x16 a vertical sockets

Technical Symbols/Marks/Approvals

IP44 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 61439-1 EN 61439-4

Description

ASC type series-assembled distribution board. Manufactured in shockproof ABS-based technopolymer. Galvanized steel DIN rail. Knockouts for pipe or cable entry with grommets, pipe fittings, or cable glands of various sizes. Supplied as standard with screw caps to ensure double insulation. Door closure with included triangular key. Produced in compliance with EN 60670-1, EN 60670-24, EN 61439-1, EN 61439-4 standards.
Recommended installation: mobile or semi-fixed. Recommended use: construction sites or temporary workplaces with access restricted to authorized personnel qualified for the specific use of the product. Equipped with angled EN 60309 sockets or bivalent/Schuko P40 sockets. 6 kA Miniature Circuit Breaker. 30 mA Type A Residual Current Device. Equipped with 4 meters of H07RN-F cable with EN 60309 plug. Rated current 16A. Protection degree IP44. Dimensions 105x337x95 mm.
1x2P+E 220V~ 16A IP44
1x3P+E 380V~ 16A IP44
1x Residual Current Circuit Breaker with Overcurrent protection (RCBO) 4P 16A 30 mA
Plug 3P+N+E 380V~ 16A IP44
5G2.5 cable
Maximum power output 10.5 kW

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


Power loss	9 W	**Leakage current type**	A	**Degree of protection (IP)**	IP44
Colour	Grey	**Width**	105 mm	**Height**	337 mm
Depth	95 mm	**Housing material**	Plastic	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Number of socket outlets with protective contact CEE 7/3 (type F)**	0
Number of socket outlets Swiss standard type 13	0	**Number of socket outlets Swiss standard type 15**	0	**Number of socket outlets Swiss standard type 23**	0
Number of socket outlets Swiss standard type 25	0	**Type of mains connection**	CEE 16 A	**Cable length**	4 m
Protection	Overcurrent switch	**Number of socket outlets Danish standard (earthing pin, type K)**	0	**CEE socket outlet 16 A**	2x16A xp xxxV
CEE socket outlet 32 A	None	**CEE socket outlet 63 A**	None	**CEE socket outlet 125 A**	None
Other fixtures and/or empty locations	0	**Earth leakage switch**	Earth leakage switch with IFN 30 mA (standard)	**Number of miniature circuit breakers (MCB)**	1
Power supply/connection possibility	Feeder cable with plug	**Number of poles mains connection**	5	**Diameter cable entry**	M25
Handling	Portable				

Technical Characteristics

Differential device	1x4P 16A	**MV protection device**	combinato	**Maximum power that can be delivered**	10.5 kW
Prese_16A_2P+T	1	**Prese_32A_2P+T**	-	**Prese_16A_3P+N+T**	-
Prese_16A_3P+T	1	**Schuko/bivalent sockets**	-	**prese_32A_3P+T**	-
Prese_32A_3P+N+T	-				

Documentation available for download

Single-line diagram



6902100-2110.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8032793875062

Unit

1 NR

0.505x0.275x0.155 [m]

2.6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.