

EC6902204



ASSEMBLED DISTR. BOARD ASC TYPE 3 VERT.SOCKETS IP44 2P+E -3P+E-ITAL.

Industrial > Distribution boards > Distribution boards > Series
acs - board system > Cee socket outlet combination (iec
60309) > 3x16a vertical sockets



Technical Symbols/Marks/Approvals



Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


Power loss	9 W	Leakage current type	AC	Degree of protection (IP)	IP44
Colour	Grey	Width	105 mm	Height	430 mm
Depth	95 mm	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	1
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE 16 A	Cable length	4 m
Protection	Overcurrent switch	Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	2x16A xp xxxV
CEE socket outlet 32 A	None	CEE socket outlet 63 A	None	CEE socket outlet 125 A	None
Other fixtures and/or empty locations	0	Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)	Number of miniature circuit breakers (MCB)	1
Power supply/connection possibility	Feeder cable with plug	Number of poles mains connection	5	Diameter cable entry	M25
Handling	Portable				

Technical Characteristics

Differential device	1 x2P 16A - 30mA	MV protection device	combinato	Maximum power that can be delivered	10.5 kW
2P+E sockets	1	3P+N+E sockets	-	3P+E sockets	1
Schuko/bivalent sockets	1				

Documentation available for download

Electical diagram



6902204.pdf

Barcode



8032793875154

Unit

1 NR

0.505x0.275x0.155 [m]

3.2 [kg]