



## EC6902304C

### ASS. DIS. BOARD ASC TYPE 4 SOCKETS IP44 4X2P+E



Industrial > Distribution boards > Distribution boards > Series  
acs - board system > Cee socket outlet combination (iec  
60309) > 4x16a sockets - with kickstand stand

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61439-1 EN 61439-4

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC000379 - CEE socket outlet combination (IEC 60309)


|                                                 |                        |                                                                 |                                                |                                                                   |               |
|-------------------------------------------------|------------------------|-----------------------------------------------------------------|------------------------------------------------|-------------------------------------------------------------------|---------------|
| Power loss                                      | 13 W                   | Leakage current type                                            | AC                                             | Degree of protection (IP)                                         | IP44          |
| Colour                                          | Grey                   | Width                                                           | 200 mm                                         | Height                                                            | 430 mm        |
| Depth                                           | 95 mm                  | Housing material                                                | Plastic                                        | Contact material                                                  | CuZn          |
| Surface coating contacts                        | Untreated              | Military model                                                  | No                                             | Number of socket outlets with protective contact CEE 7/3 (type F) | 0             |
| Number of socket outlets Swiss standard type 13 | 0                      | Number of socket outlets Swiss standard type 15                 | 0                                              | Number of socket outlets Swiss standard type 23                   | 0             |
| Number of socket outlets Swiss standard type 25 | 0                      | Type of mains connection                                        | CEE 16 A                                       | Cable length                                                      | 4 m           |
| Protection                                      | Overcurrent switch     | Number of socket outlets Danish standard (earthing pin, type K) | 0                                              | CEE socket outlet 16 A                                            | 4x16A xp xxxV |
| CEE socket outlet 32 A                          | None                   | CEE socket outlet 63 A                                          | None                                           | CEE socket outlet 125 A                                           | None          |
| Other fixtures and/or empty locations           | 0                      | Earth leakage switch                                            | Earth leakage switch with IFN 30 mA (standard) | Number of miniature circuit breakers (MCB)                        | 1             |
| Power supply/connection possibility             | Feeder cable with plug | Number of poles mains connection                                | 3                                              | Diameter cable entry                                              | M25           |
| Handling                                        | Portable               |                                                                 |                                                |                                                                   |               |

## Technical Characteristics

|                         |                  |                      |           |                                     |        |
|-------------------------|------------------|----------------------|-----------|-------------------------------------|--------|
| Differential device     | 1 x2P 16A - 30mA | MV protection device | combinato | Maximum power that can be delivered | 3.6 kW |
| 2P+E sockets            | 4                | 3P+N+E sockets       | -         | 3P+E sockets                        | -      |
| Schuko/bivalent sockets | -                |                      |           |                                     |        |

## Documentation available for download

### Electrical diagram



6902304-2313.pdf

## Barcode



8033954873200

**Unit**

1 NR

6.5 [kg]