



**EC6902323**

## ASS. DIS. BOARD DBO TYPE 4 SOCKETS IP44 2X2P+E - 2 ITAL.

Industrial > Distribution boards > Distribution boards > Series  
dbo - board system > Cee socket outlet combination (iec  
60309) > 4x16 a sockets



### Technical Symbols/Marks/Approvals



### Norms

EN 61439-1 EN 61439-3

## Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


|                                                                 |           |                                                 |             |                                                                   |                       |
|-----------------------------------------------------------------|-----------|-------------------------------------------------|-------------|-------------------------------------------------------------------|-----------------------|
| Power loss                                                      | 13 W      | Leakage current type                            | Other       | Degree of protection (IP)                                         | IP44                  |
| Colour                                                          | Grey      | Width                                           | 200 mm      | Height                                                            | 430 mm                |
| Depth                                                           | 95 mm     | Housing material                                | Plastic     | Contact material                                                  | CuZn                  |
| Surface coating contacts                                        | Untreated | Military model                                  | No          | Number of socket outlets with protective contact CEE 7/3 (type F) | 2                     |
| Number of socket outlets Swiss standard type 13                 | 0         | Number of socket outlets Swiss standard type 15 | 0           | Number of socket outlets Swiss standard type 23                   | 0                     |
| Number of socket outlets Swiss standard type 25                 | 0         | Type of mains connection                        | Other       | Protection                                                        | Overcurrent switch    |
| Number of socket outlets Danish standard (earthing pin, type K) | 0         | CEE socket outlet 16 A                          | 2x16A3p230V | CEE socket outlet 32 A                                            | None                  |
| CEE socket outlet 63 A                                          | None      | CEE socket outlet 125 A                         | None        | Other fixtures and/or empty locations                             | 0                     |
| Earth leakage switch                                            | None      | Number of miniature circuit breakers (MCB)      | 1           | Power supply/connection possibility                               | 1 cable (branch line) |
| Number of poles mains connection                                | 2         | Diameter cable entry                            | M25         | Handling                                                          | Wall mounting         |

## Technical Characteristics

|                      |          |                                     |        |                         |   |
|----------------------|----------|-------------------------------------|--------|-------------------------|---|
| MV protection device | 1x2P 16A | Maximum power that can be delivered | 3.6 kW | Prese_16A_2P+T          | 2 |
| Prese_16A_3P+N+T     | -        | Prese_16A_3P+T                      | -      | Schuko/bivalent sockets | 2 |

## Documentation available for download

Electical diagram



6902323.pdf

## Barcode



8032793874881

**Unit**

1 NR

0.505x0.275x0.155 [m]

2.75 [kg]