



**EC6902404**

## ASS. DIS. BOARD ASC TYPE 3 SOCKETS IP44 3X2P+E

Industrial > Distribution boards > Distribution boards > Series  
acs - board system > Cee socket outlet combination (iec  
60309) > 3x16 a horizontal sockets



### Technical Symbols/Marks/Approvals



### Norms

EN 61439-1 EN 61439-4

## Etim

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC000379 - CEE socket outlet combination (IEC 60309)**

|                                                        |                        |                                                                        |                                                |                                                                          |             |
|--------------------------------------------------------|------------------------|------------------------------------------------------------------------|------------------------------------------------|--------------------------------------------------------------------------|-------------|
| <b>Power loss</b>                                      | 24 W                   | <b>Leakage current type</b>                                            | AC                                             | <b>Degree of protection (IP)</b>                                         | IP44        |
| <b>Colour</b>                                          | Grey                   | <b>Width</b>                                                           | 360 mm                                         | <b>Height</b>                                                            | 320 mm      |
| <b>Depth</b>                                           | 135 mm                 | <b>Housing material</b>                                                | Plastic                                        | <b>Contact material</b>                                                  | CuZn        |
| <b>Surface coating contacts</b>                        | Untreated              | <b>Military model</b>                                                  | No                                             | <b>Number of socket outlets with protective contact CEE 7/3 (type F)</b> | 0           |
| <b>Number of socket outlets Swiss standard type 13</b> | 0                      | <b>Number of socket outlets Swiss standard type 15</b>                 | 0                                              | <b>Number of socket outlets Swiss standard type 23</b>                   | 0           |
| <b>Number of socket outlets Swiss standard type 25</b> | 0                      | <b>Type of mains connection</b>                                        | CEE 16 A                                       | <b>Cable length</b>                                                      | 4 m         |
| <b>Protection</b>                                      | Overcurrent switch     | <b>Number of socket outlets Danish standard (earthing pin, type K)</b> | 0                                              | <b>CEE socket outlet 16 A</b>                                            | 2x16A3p230V |
| <b>CEE socket outlet 32 A</b>                          | None                   | <b>CEE socket outlet 63 A</b>                                          | None                                           | <b>CEE socket outlet 125 A</b>                                           | None        |
| <b>Other fixtures and/or empty locations</b>           | 0                      | <b>Earth leakage switch</b>                                            | Earth leakage switch with IFN 30 mA (standard) | <b>Number of miniature circuit breakers (MCB)</b>                        | 1           |
| <b>Power supply/connection possibility</b>             | Feeder cable with plug | <b>Number of poles mains connection</b>                                | 3                                              | <b>Diameter cable entry</b>                                              | M32         |
| <b>Handling</b>                                        | Portable               |                                                                        |                                                |                                                                          |             |

## Technical Characteristics

|                            |                  |                                |           |                                            |        |
|----------------------------|------------------|--------------------------------|-----------|--------------------------------------------|--------|
| <b>Differential device</b> | 1 x2P 16A - 30mA | <b>MV protection device</b>    | combinato | <b>Maximum power that can be delivered</b> | 3.6 kW |
| <b>Prese_16A_2P+T</b>      | 3                | <b>Prese_32A_2P+T</b>          | -         | <b>Prese_16A_3P+N+T</b>                    | -      |
| <b>Prese_16A_3P+T</b>      | -                | <b>Schuko/bivalent sockets</b> | -         | <b>prese_32A_3P+T</b>                      | -      |
| <b>Prese_32A_3P+N+T</b>    | -                |                                |           |                                            |        |

## Documentation available for download

### Electical diagram



6902404-2413.pdf

## Barcode



8032793875871

### Unit

1 NR

4.6 [kg]