

EC6902422



**ASS. DIS. BOARD DBO TYPE 3
SOCKETS IP44 2P+E -3P+E -3P+N+E**

Industrial > Distribution boards > Distribution boards > Series dbo - board system > Cee socket outlet combination (iec 60309) > 3x16 a horizontal sockets



Technical Symbols/Marks/Approvals



Norms

EN 61439-1 EN 61439-3

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


| | | | | | |
|--|-----------|--|---------------|--|-----------------------|
| Power loss | 24 W | Leakage current type | Other | Degree of protection (IP) | IP44 |
| Colour | Grey | Width | 360 mm | Height | 320 mm |
| Depth | 135 mm | Housing material | Plastic | Contact material | CuZn |
| Surface coating contacts | Untreated | Military model | No | Number of socket outlets with protective contact CEE 7/3 (type F) | 0 |
| Number of socket outlets Swiss standard type 13 | 0 | Number of socket outlets Swiss standard type 15 | 0 | Number of socket outlets Swiss standard type 23 | 0 |
| Number of socket outlets Swiss standard type 25 | 0 | Type of mains connection | Other | Protection | Overcurrent switch |
| Number of socket outlets Danish standard (earthing pin, type K) | 0 | CEE socket outlet 16 A | 3x16A xp xxxV | CEE socket outlet 32 A | None |
| CEE socket outlet 63 A | None | CEE socket outlet 125 A | None | Other fixtures and/or empty locations | 0 |
| Earth leakage switch | None | Number of miniature circuit breakers (MCB) | 1 | Power supply/connection possibility | 1 cable (branch line) |
| Number of poles mains connection | 4 | Diameter cable entry | M32 | Handling | Wall mounting |

Technical Characteristics

| | | | | | |
|----------------------|----------|-------------------------------------|---------|-------------------------|---|
| MV protection device | 1x4P 16A | Maximum power that can be delivered | 10.5 kW | Prese_16A_2P+T | 1 |
| Prese_16A_3P+N+T | 1 | Prese_16A_3P+T | 1 | Schuko/bivalent sockets | - |

Documentation available for download

Electical diagram



6902422-2432.pdf

Barcode



8032793874942

Unit

1 NR

3.6 [kg]