



## EC6902450

### ASS. DIS. BOARD ASC TYPE 2 SOCKETS IP65 2X2P+E



Industrial > Distribution boards > Distribution boards > Series  
acs - board system > Cee socket outlet combination (iec  
60309) > 2x16 a horizontal interlocked sockets

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61439-1 EN 61439-4

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC000379 - CEE socket outlet combination (IEC 60309)


|                                                 |                        |                                                                 |                                                |                                                                   |             |
|-------------------------------------------------|------------------------|-----------------------------------------------------------------|------------------------------------------------|-------------------------------------------------------------------|-------------|
| Power loss                                      | 24 W                   | Leakage current type                                            | AC                                             | Degree of protection (IP)                                         | IP65        |
| Colour                                          | Grey                   | Width                                                           | 360 mm                                         | Height                                                            | 320 mm      |
| Depth                                           | 135 mm                 | Housing material                                                | Plastic                                        | Contact material                                                  | CuZn        |
| Surface coating contacts                        | Untreated              | Military model                                                  | No                                             | Number of socket outlets with protective contact CEE 7/3 (type F) | 0           |
| Number of socket outlets Swiss standard type 13 | 0                      | Number of socket outlets Swiss standard type 15                 | 0                                              | Number of socket outlets Swiss standard type 23                   | 0           |
| Number of socket outlets Swiss standard type 25 | 0                      | Type of mains connection                                        | CEE 16 A                                       | Cable length                                                      | 4 m         |
| Protection                                      | Overcurrent switch     | Number of socket outlets Danish standard (earthing pin, type K) | 0                                              | CEE socket outlet 16 A                                            | 2x16A3p230V |
| CEE socket outlet 32 A                          | None                   | CEE socket outlet 63 A                                          | None                                           | CEE socket outlet 125 A                                           | None        |
| Other fixtures and/or empty locations           | 0                      | Earth leakage switch                                            | Earth leakage switch with IFN 30 mA (standard) | Number of miniature circuit breakers (MCB)                        | 1           |
| Power supply/connection possibility             | Feeder cable with plug | Number of poles mains connection                                | 3                                              | Diameter cable entry                                              | M32         |
| Handling                                        | Portable               |                                                                 |                                                |                                                                   |             |

## Technical Characteristics

|                            |                  |                                |           |                                            |        |
|----------------------------|------------------|--------------------------------|-----------|--------------------------------------------|--------|
| <b>Differential device</b> | 1x2P 16A - 30 mA | <b>MV protection device</b>    | combinato | <b>Maximum power that can be delivered</b> | 3.6 kW |
| <b>Prese_16A_2P+T</b>      | 2                | <b>Prese_32A_2P+T</b>          | -         | <b>Prese_16A_3P+N+T</b>                    | -      |
| <b>Prese_16A_3P+T</b>      | -                | <b>Schuko/bivalent sockets</b> | -         | <b>prese_32A_3P+T</b>                      | -      |
| <b>Prese_32A_3P+N+T</b>    | -                |                                |           |                                            |        |

## Documentation available for download

### Electical diagram



6902440-2450.pdf

## Barcode



8032793875949

### Unit

1 NR

5 [kg]