



## EC6902462

### ASS. DIS. BOARD DBO TYPE 2 SOCKETS IP44 1X2P+E -1X3P+E



Industrial > Distribution boards > Distribution boards > Series dbo - board system > Cee socket outlet combination (iec 60309) > 2x16 a horizontal interlocked sockets

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61439-1 EN 61439-3

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC000379 - CEE socket outlet combination (IEC 60309)

|   |           |   |               |   |                       |
|---|-----------|---|---------------|---|-----------------------|
| Power loss  | 24 W      | Leakage current type                            | Other         | Degree of protection (IP)   | IP44                  |
| Colour  | Grey      | Width   | 360 mm        | Height  | 320 mm                |
| Depth   | 135 mm    | Housing material                                | Plastic       | Contact material  | CuZn                  |
| Surface coating contacts  | Untreated | Military model                                  | No            | Number of socket outlets with protective contact CEE 7/3 (type F) | 0                     |
| Number of socket outlets Swiss standard type 13                 | 0         | Number of socket outlets Swiss standard type 15 | 0             | Number of socket outlets Swiss standard type 23                   | 0                     |
| Number of socket outlets Swiss standard type 25                 | 0         | Type of mains connection                        | Other         | Protection  | Overcurrent switch    |
| Number of socket outlets Danish standard (earthing pin, type K) | 0         | CEE socket outlet 16 A                          | 2x16A xp xxxV | CEE socket outlet 32 A  | None                  |
| CEE socket outlet 63 A  | None      | CEE socket outlet 125 A                         | None          | Other fixtures and/or empty locations                             | 0                     |
| Earth leakage switch  | None      | Number of miniature circuit breakers (MCB)      | 1             | Power supply/connection possibility                               | 1 cable (branch line) |
| Number of poles mains connection                                | 4         | Diameter cable entry                            | M32           | Handling  | Wall mounting         |

## Technical Characteristics

|                         |          |                                     |         |                |   |
|-------------------------|----------|-------------------------------------|---------|----------------|---|
| MV protection device    | 1x4P 16A | Maximum power that can be delivered | 10.5 kW | Prese_16A_2P+T | 1 |
| Prese_32A_2P+T          | -        | Prese_16A_3P+N+T                    | -       | Prese_16A_3P+T | 1 |
| Schuko/bivalent sockets | -        | Prese_32A_3P+N+T                    | -       |                |   |

## Documentation available for download

**Electical diagram**  
6902462-2472.pdf



## Barcode



8032793875598  
**Unit**  
1 NR  
4 [kg]