



EC6902510

ASSEMBLED DISTR. BOARD ASC TYPE 6 SOCKETS IP44 6X3P+E

Industrial > Distribution boards > Distribution boards > Asc -
board system > Cee socket combination (iec 60309) > 6
sockets - 16a



Technical Symbols/Marks/Approvals

GWT 650°		IP65
-------------	--	------

Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)

Height	510 mm	Colour	Grey	Width	320 mm
Depth	135 mm	Degree of protection (IP)	IP65	Housing material	Plastic
Number of socket outlets with protective contact CEE 7/3 (type F)	0	Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0	Number of miniature circuit breakers (MCB)	2
Leakage current type	AC	CEE socket outlet 16 A	> 4x16A xp xxxV	CEE socket outlet 32 A	None
CEE socket outlet 63 A	None	CEE socket outlet 125 A	None	Number of socket outlets Danish standard (earthing pin, type K)	0
Other fixtures and/or empty locations	0	Power loss	24 W	Protection	Overcurrent switch
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)	Contact material	CuZn	Surface treatment contacts	Untreated
Surface coating contacts	Untreated	Power supply/connection possibility	Feeder cable with plug	Number of poles mains connection	5
Diameter cable entry	M32	Type of mains connection	CEE 16 A	Cable length	4 m
Handling	Portable	Military model	No		

Documentation available for download

Electical diagram



6902500-2510.pdf

Barcode



8032793875376

1 NR

6.8 [kg]