



EC6902513

ASSEMBLED DISTR. BOARD ASC TYPE 6 SOCKETS IP65 6X2P+E

Industrial > Distribution boards > Distribution boards > Series
acs - board system > Cee socket outlet combination (iec
60309) > 6x16 a sockets



Technical Symbols/Marks/Approvals



Norms

EN 61439-1 EN 61439-4

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)

Power loss	24 W	Leakage current type	AC	Degree of protection (IP)	IP65
Colour	Grey	Width	320 mm	Height	510 mm
Depth	135 mm	Housing material	Plastic	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE 16 A	Cable length	4 m
Protection	Overcurrent switch	Number of socket outlets Danish standard (earthing pin, type K)	0	CEE socket outlet 16 A	> 4x16A3p230V
CEE socket outlet 32 A	None	CEE socket outlet 63 A	None	CEE socket outlet 125 A	None
Other fixtures and/or empty locations	0	Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)	Number of miniature circuit breakers (MCB)	2
Power supply/connection possibility	Feeder cable with plug	Number of poles mains connection	3	Diameter cable entry	M32
Handling	Portable				


Technical Characteristics

Differential device	1x2P 40A - 30 mA	MV protection device	2x2P	Maximum power that can be delivered	3.6 kW
Prese_16A_2P+T	6	Prese_32A_2P+T	-	Prese_16A_3P+N+T	-
Prese_16A_3P+T	-	Schuko/bivalent sockets	-	prese_32A_3P+T	-
Prese_32A_3P+N+T	-				

Documentation available for download

Electical diagram

6902504-2513.pdf



Barcode



8032793875994

Unit

1 NR

6.9 [kg]