



## EC6902523

### ASSEMBLED DISTR. BOARD DBO TYPE 6 SOCKETS IP44 2X2P+E -3P+N+E-2 ITAL.



Industrial > Distribution boards > Distribution boards > Series  
dbo - board system > Cee socket outlet combination (iec  
60309) > 6x16 a sockets

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61439-1 EN 61439-3

## Etim

### GROUP EG000014 - Industrial sockets/plug applications


### CLASS EC000379 - CEE socket outlet combination (IEC 60309)

|                                                                        |           |                                                        |               |                                                                          |                       |
|------------------------------------------------------------------------|-----------|--------------------------------------------------------|---------------|--------------------------------------------------------------------------|-----------------------|
| <b>Power loss</b>                                                      | 24 W      | <b>Leakage current type</b>                            | Other         | <b>Degree of protection (IP)</b>                                         | IP44                  |
| <b>Colour</b>                                                          | Grey      | <b>Width</b>                                           | 320 mm        | <b>Height</b>                                                            | 510 mm                |
| <b>Depth</b>                                                           | 135 mm    | <b>Housing material</b>                                | Plastic       | <b>Contact material</b>                                                  | CuZn                  |
| <b>Surface coating contacts</b>                                        | Untreated | <b>Military model</b>                                  | No            | <b>Number of socket outlets with protective contact CEE 7/3 (type F)</b> | 2                     |
| <b>Number of socket outlets Swiss standard type 13</b>                 | 0         | <b>Number of socket outlets Swiss standard type 15</b> | 0             | <b>Number of socket outlets Swiss standard type 23</b>                   | 0                     |
| <b>Number of socket outlets Swiss standard type 25</b>                 | 0         | <b>Type of mains connection</b>                        | Other         | <b>Protection</b>                                                        | Overcurrent switch    |
| <b>Number of socket outlets Danish standard (earthing pin, type K)</b> | 0         | <b>CEE socket outlet 16 A</b>                          | 4x16A xp xxxV | <b>CEE socket outlet 32 A</b>                                            | None                  |
| <b>CEE socket outlet 63 A</b>                                          | None      | <b>CEE socket outlet 125 A</b>                         | None          | <b>Other fixtures and/or empty locations</b>                             | 0                     |
| <b>Earth leakage switch</b>                                            | None      | <b>Number of miniature circuit breakers (MCB)</b>      | 2             | <b>Power supply/connection possibility</b>                               | 1 cable (branch line) |
| <b>Number of poles mains connection</b>                                | 4         | <b>Diameter cable entry</b>                            | M32           | <b>Handling</b>                                                          | Wall mounting         |

## Technical Characteristics

|                      |                     |                                     |         |                         |   |
|----------------------|---------------------|-------------------------------------|---------|-------------------------|---|
| MV protection device | 1x2P 16A + 1x4P 16A | Maximum power that can be delivered | 14.1 kW | Prese_16A_2P+T          | 2 |
| Prese_16A_3P+N+T     | 1                   | Prese_16A_3P+T                      | 1       | Schuko/bivalent sockets | 2 |

## Documentation available for download



## Barcode

