

EC6902555

ASS. DIS. BOARD ASC TYPE 4 SOCKETS IP65 2X2P+E -1X3P+E 16 - 1X3P +N 32

Industrial > Distribution boards > Distribution boards > Series asc - board system > Cee socket outlet combination (iec 60309) > 4x16 a - 32 a horizontal interlocked sockets

Technical Symbols/Marks/Approvals

IP65 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 61439-1 EN 61439-4

Description

ASC-type serial-assembled distribution board. Made of impact-resistant ABS-based technopolymer. Galvanized steel DIN rail. Knockouts for conduit or cable entry with grommets, conduit fittings, or cable glands of various sizes. Supplied as standard with screw caps to ensure double insulation. Door closure with included triangular key. Manufactured in compliance with EN60670-1, EN 60670-24, EN 61439-1, and EN 61439-4 standards.
Recommended installation: mobile or semi-fixed. Recommended use: construction sites or temporary workplaces with access restricted to authorized personnel qualified for the specific use of the product. Equipped with horizontal interlocked EN 60309 sockets without fuse base. 6 kA miniature circuit breaker (MCB) protection. 30 mA Type A residual current device (RCD) protection. Equipped with 4 m of H07RN-F cable with EN 60309 plug. Mounted carrying handle. Rated current: 32A. Protection rating: IP65. Dimensions: 320x510x135 mm.
2x2P+E 220V~ 16A IP65
1x3P+E 380V~ 16A IP65
1x3P+N+E 380V~ 32A IP65
1x 4P 40A 30 mA Residual Current Circuit Breaker (RCCB)
1x 2P 16A Miniature Circuit Breaker (MCB)
1x 3P 16A Miniature Circuit Breaker (MCB)
1x 4P 32A Miniature Circuit Breaker (MCB)
3P+N+E 380V~ 32A IP67 Plug
5G4 Cable
Maximum deliverable power: 21.0 kW

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC000379 - CEE socket outlet combination (IEC 60309)


Power loss	24 W	**Leakage current type**	A	**Degree of protection (IP)**	IP65
Colour	Grey	**Width**	320 mm	**Height**	510 mm
Depth	135 mm	**Housing material**	Plastic	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Number of socket outlets with protective contact CEE 7/3 (type F)**	0
Number of socket outlets Swiss standard type 13	0	**Number of socket outlets Swiss standard type 15**	0	**Number of socket outlets Swiss standard type 23**	0
Number of socket outlets Swiss standard type 25	0	**Type of mains connection**	CEE 32 A	**Cable length**	4 m
Protection	Overcurrent switch	**Number of socket outlets Danish standard (earthing pin, type K)**	0	**CEE socket outlet 16 A**	3x16A xp xxxV
CEE socket outlet 32 A	1x32A5p400V	**CEE socket outlet 63 A**	None	**CEE socket outlet 125 A**	None
Other fixtures and/or empty locations	0	**Earth leakage switch**	Earth leakage switch with IFN 30 mA (standard)	**Number of miniature circuit breakers (MCB)**	3
Power supply/connection possibility	Feeder cable with plug	**Number of poles mains connection**	5	**Diameter cable entry**	M32
Handling	Portable				

Technical Characteristics

Differential device	1x4P 40A	**MV protection device**	1x2P 16A + 1x3P 16A +1x4P 32A	**Maximum power that can be delivered**	21.0 kW
Prese_16A_2P+T	2	**Prese_32A_2P+T**	-	**Prese_16A_3P+N+T**	-
Prese_16A_3P+T	1	**Schuko/bivalent sockets**	-	**prese_32A_3P+T**	-
Prese_32A_3P+N+T	1				

Documentation available for download

Single-line diagram



6902545-2555.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8032793871835

Unit

1 NR

7.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.