

## EC6902573

### ASS. DIS. BOARD DBO TYPE 4 SOCKETS IP65 4X3P+E

Industrial > Distribution boards > Distribution boards > Series dbo - board system > Cee socket outlet combination (iec 60309) > 4x16a horizontal interlocked sockets



#### Technical Symbols/Marks/Approvals



#### Norms

EN 61439-1 EN 61439-3

#### Etim

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC000379 - CEE socket outlet combination (IEC 60309)**

|                                                                 |           |                                                 |               |                                                                   |                       |
|-----------------------------------------------------------------|-----------|-------------------------------------------------|---------------|-------------------------------------------------------------------|-----------------------|
| Power loss                                                      | 24 W      | Leakage current type                            | Other         | Degree of protection (IP)                                         | IP65                  |
| Colour                                                          | Grey      | Width                                           | 320 mm        | Height                                                            | 510 mm                |
| Depth                                                           | 135 mm    | Housing material                                | Plastic       | Contact material                                                  | CuZn                  |
| Surface coating contacts                                        | Untreated | Military model                                  | No            | Number of socket outlets with protective contact CEE 7/3 (type F) | 0                     |
| Number of socket outlets Swiss standard type 13                 | 0         | Number of socket outlets Swiss standard type 15 | 0             | Number of socket outlets Swiss standard type 23                   | 0                     |
| Number of socket outlets Swiss standard type 25                 | 0         | Type of mains connection                        | Other         | Protection                                                        | Overcurrent switch    |
| Number of socket outlets Danish standard (earthing pin, type K) | 0         | CEE socket outlet 16 A                          | 4x16A xp xxxV | CEE socket outlet 32 A                                            | None                  |
| CEE socket outlet 63 A                                          | None      | CEE socket outlet 125 A                         | None          | Other fixtures and/or empty locations                             | 0                     |
| Earth leakage switch                                            | None      | Number of miniature circuit breakers (MCB)      | 2             | Power supply/connection possibility                               | 1 cable (branch line) |
| Number of poles mains connection                                | 3         | Diameter cable entry                            | M32           | Handling                                                          | Wall mounting         |

#### Technical Characteristics

|                      |          |                                     |         |                         |   |
|----------------------|----------|-------------------------------------|---------|-------------------------|---|
| MV protection device | 2x3P 16A | Maximum power that can be delivered | 21.0 kW | Prese_16A_2P+T          | - |
| Prese_16A_3P+N+T     | -        | Prese_16A_3P+T                      | 4       | Schuko/bivalent sockets | - |

## Documentation available for download

### Electical diagram



6902563-2573.pdf

## Barcode



8032793875741

### Unit

1 NR

5 [kg]