



**EC6904511**



**ASS. DIS. BOARD ASC TYPE 2  
SOCKETS IP44 1X3P+E -1X3P+N+E 32**

Industrial > Distribution boards > Distribution boards > Series  
acs - board system > Cee socket outlet combination (iec  
60309) > 2 x 16 a / 32 a vertical interlocked sockets - with fuse  
holder

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61439-1 EN 61439-4

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC000379 - CEE socket outlet combination (IEC 60309)**

|                                                        |                              |                                                                        |                                                |                                                                          |        |
|--------------------------------------------------------|------------------------------|------------------------------------------------------------------------|------------------------------------------------|--------------------------------------------------------------------------|--------|
| <b>Power loss</b>                                      | 24 W                         | <b>Leakage current type</b>                                            | AC                                             | <b>Degree of protection (IP)</b>                                         | IP44   |
| <b>Colour</b>                                          | Grey                         | <b>Width</b>                                                           | 320 mm                                         | <b>Height</b>                                                            | 510 mm |
| <b>Depth</b>                                           | 135 mm                       | <b>Housing material</b>                                                | Plastic                                        | <b>Contact material</b>                                                  | CuZn   |
| <b>Surface coating contacts</b>                        | Untreated                    | <b>Military model</b>                                                  | No                                             | <b>Number of socket outlets with protective contact CEE 7/3 (type F)</b> | 0      |
| <b>Number of socket outlets Swiss standard type 13</b> | 0                            | <b>Number of socket outlets Swiss standard type 15</b>                 | 0                                              | <b>Number of socket outlets Swiss standard type 23</b>                   | 0      |
| <b>Number of socket outlets Swiss standard type 25</b> | 0                            | <b>Type of mains connection</b>                                        | CEE 32 A                                       | <b>Cable length</b>                                                      | 4 m    |
| <b>Protection</b>                                      | Overcurrent switch/D0-system | <b>Number of socket outlets Danish standard (earthing pin, type K)</b> | 0                                              | <b>CEE socket outlet 16 A</b>                                            | None   |
| <b>CEE socket outlet 32 A</b>                          | 2x32A xp xxxV                | <b>CEE socket outlet 63 A</b>                                          | None                                           | <b>CEE socket outlet 125 A</b>                                           | None   |
| <b>Other fixtures and/or empty locations</b>           | 0                            | <b>Earth leakage switch</b>                                            | Earth leakage switch with IFN 30 mA (standard) | <b>Number of miniature circuit breakers (MCB)</b>                        | 0      |
| <b>Power supply/connection possibility</b>             | Feeder cable with plug       | <b>Number of poles mains connection</b>                                | 5                                              | <b>Diameter cable entry</b>                                              | M32    |
| <b>Handling</b>                                        | Portable                     |                                                                        |                                                |                                                                          |        |

## Technical Characteristics

|                         |                  |                                     |         |                  |   |
|-------------------------|------------------|-------------------------------------|---------|------------------|---|
| Differential device     | 1x4P 40A - 30 mA | Maximum power that can be delivered | 21.0 kW | Prese_16A_2P+T   | - |
| Prese_32A_2P+T          | -                | Prese_16A_3P+N+T                    | -       | Prese_16A_3P+T   | - |
| Schuko/bivalent sockets | -                | prese_32A_3P+T                      | 1       | Prese_32A_3P+N+T | 1 |

## Documentation available for download

### Electical diagram



6904511-4531.pdf

## Barcode



8033954870841

### Unit

1 NR

4 [kg]