

EC690914

PANEL-MOUNT VERT. INTERLOCKED SOCKET IP65 220V 2P+E 16A

Industrial > Plugs and sockets > Switched interlocked > Vertical - without fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - flush-mount

Technical Symbols/Marks/Approvals

IP65 | IK08 | HF | CE | RoHS II | MADE IN ITALY

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Flush-mounted fixed interlocked socket. IP65 protection rating. Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 20° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 2P+E 16A 200-250V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	3	**Degree of protection (IP)**	IP65	**Model**	Top cover
Housing material	Plastic	**IEC-amperage**	16 A	**Voltage according to EN 60309-2**	230 V (50+60 Hz) blue
Clock hour position	6 h	**Identification colour**	Blue	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Protection**	None
Switch	Mechanical locking	**With earth leakage switch**	No	**Empty locations on mounting rail**	No

Documentation available for download



Certification

IMQ_CA02.05813_2025_16A_IVSBF.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8053676575947

Unit

1 NR

0.295x0.12x0.15 [m]

0.68 [kg]

8059307216531

Cardboard

10 NR

0.605x0.4x0.35 [m]

6.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.