

EC69093

PANEL-MOUNT HORIZ. INTERLOCKED SOCKET IP65 380V 3P+E 16A

Industrial > Plugs and sockets > Switched interlocked > Horizontal - without fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - wall-mount

Technical Symbols/Marks/Approvals

IP65 | IK08 | HF | CE | RoHS II | MADE IN ITALY

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Interlocked switched flush-mounting socket. Protection rating IP65. Dimensions: 155x115x24 mm. Fixing centres 138x98 mm. 20° inclined socket. Switch type AC23A - 10 kA. Ergonomic handle padlockable in ON/OFF position. Stainless steel cover springs. 3P+E 16A 380-415V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	4	**Degree of protection (IP)**	IP65	**Model**	Top cover
Housing material	Plastic	**IEC-amperage**	16 A	**Voltage according to EN 60309-2**	400 V (50+60 Hz) red
Clock hour position	6 h	**Identification colour**	Red	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Protection**	None
Switch	Mechanical locking	**With earth leakage switch**	No	**Empty locations on mounting rail**	No

Documentation available for download



Certification

IMQ_CA02.05703_2025_16AIOSBF.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8032636763457

Unit

1 NR

0.125x0.19x0.135 [m]

0.5 [kg]



8059307216678

Cardboard

24 NR

0.415x0.6x0.44 [m]

12 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.