

# EC69097

## PANEL-MOUNT HORIZ. INTERLOCKED SOCKET IP65 380V 3P+E 32A

Industrial > Plugs and sockets > Switched interlocked > Horizontal - without fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - wall-mount

### Technical Symbols/Marks/Approvals

IP65 | IK08 | HF | CE | RoHS II | MADE IN ITALY

### Norms

EN 60309-1 EN 60309-2 EN 60309-4

## Description

Interlocked switched flush-mounting socket. Protection rating IP65. Dimensions: 155x115x24 mm. Fixing centres 138x98 mm. 20° inclined socket. Switch type AC23A - 10 kA. Ergonomic handle padlockable in ON/OFF position. Stainless steel cover springs. 3P+E 32A 380-415V~ 6h

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

| | | | | | |
|---|---|---|---|---|---|
| **Number of poles** | 4 | **Degree of protection (IP)** | IP65 | **Model** | Top cover |
| **Housing material** | Plastic | **IEC-amperage** | 32 A | **Voltage according to EN 60309-2** | 400 V (50+60 Hz) red |
| **Clock hour position** | 6 h | **Identification colour** | Red | **Contact material** | CuZn |
| **Surface coating contacts** | Untreated | **Military model** | No | **Protection** | None |
| **Switch** | Mechanical locking | **With earth leakage switch** | No | **Empty locations on mounting rail** | No |

## Documentation available for download



Certification

IMQ_CA02.05700_2025_32A_IOSBF.pdf



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8032636764263
**Unit**
1 NR
0.17x0.12x0.12 [m]
0.5 [kg]

8059307217002
**Cardboard**
24 NR
0.6x0.415x0.44 [m]
12 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.