THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC690FU16

10X38 FUSE GG - 16A

Industrial > Plugs and sockets > Switched interlocked > Accessories for interlocked sockets > Cylindrical fuse

Technical Symbols/Marks/Approvals

CE | RoHS II | MADE IN EU

Norms

IEC 60269-2-1 UNE 21103 CEI 32/1-4 NCF 63210

Description

gG type fuse. Dimensions 10x38 mm. Rated current 16A. Rated voltage 500V. For use in 16A and 32A horizontal and vertical interlocked sockets.

Etim

GROUP EG000020 - Circuit breakers and fuses

CLASS EC002704 - Cylindrical fuse

Rated voltage	500 V	**Rated current**	16 A	**Voltage type**	AC
Model	Ceramic fuse	**Release characteristic**	Fast (F)	**Size**	10x38 mm
Utilization category according to IEC 60269	gG	**Rated operating frequency**	50 ÷ 60 Hz	**Type of fuse status indicator**	Other
Breaking capacity	120 kA				

Barcode

8056351662994

Pack

10 NR

0.05 [kg]

8050880883356

Cardboard

50 NR

0.25 [kg]

ELETTROCANALI s.p.a. | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.