

EC690FU63

15X36 FUSE GG - 63A

Industrial > Plugs and sockets > Switched interlocked > Accessories for interlocked sockets > Cylindrical fuse

Technical Symbols/Marks/Approvals

CE | RoHS II | MADE IN EU

Norms

IEC 60269-3-1 | DIN VDE 0636-301 | DIN EN 60269.1/3 | EN 60947-1/60947-3

Description

D02 gG type fuse. Dimensions 15x36 mm. Rated current 63A. Rated voltage 500V. For use in 63A vertical interlocked sockets.

Etim

GROUP EG000020 - Circuit breakers and fuses

CLASS EC002704 - Cylindrical fuse

Rated voltage	400 V	**Rated current**	62 A	**Voltage type**	AC
Model	Ceramic fuse	**Release characteristic**	Fast (F)	**Size**	Other
Utilization category according to IEC 60269	gG	**Rated operating frequency**	50 ÷ 60 Hz	**Type of fuse status indicator**	Centre fuse status indicator
Breaking capacity	50 kA				

Barcode

8056351663014
Pack
10 NR
0.05 [kg]

8050880883370
Cardboard
50 NR
0.25 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.