

EC6910808

DISTR. BOARD FOR CONSTRUCTION SITE 2X2P16-1X3P16-3X3P+N32

Industrial > Distribution boards > Distribution boards > Series acs - panel system 800 > Energy distributor for construction site > 6 vertical interlocked sockets - power supply with terminal block

Technical Symbols/Marks/Approvals

IP65 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 61439-1 EN 61439-4

Description

ASC-type distribution board, factory-assembled in series. Manufactured in shock-resistant, two-component technopolymer. IK10 impact resistance rating, suitable for heavy-duty applications. Galvanized steel DIN rail. Double door closure with triangular key included. MCB protection for outlets located in a control panel with a triangular lock, key included. Wall-mounting capability via metal brackets or on a metal stand. Carrying handles integrated into the casing. Open base for cable exit. Operation possible with plugs inserted even when the door is closed. 180° door opening angle. Manufactured in compliance with EN 60670-1, EN 60670-24, EN 61439-1, EN 61439-4 standards.
Recommended installation: mobile or semi-fixed. Recommended use: construction sites or temporary workplaces where access is restricted to authorized and qualified personnel. Equipped with EN 60309 vertical interlocked sockets with fuse base. gG 10.3x38 fuses not supplied. MCB protection device 80-100-125A. 30 mA type AC RCD protection device. Emergency stop button with twist-to-reset and shunt trip coil. Wired external earthing terminal. M40 cable gland. Rated current 125A. Protection degree IP65. Dimensions 870x720x375 mm.
2x2P+E 220V~ 16A IP65
1x3P+E 380V~ 16A IP65
3x3P+N+E 380V~ 32A IP65
1x Main MCB 4P 125A 10kA
2x RCD 4P 63A 30 mA
Power supply via 35 mm2 terminal block
Maximum power output 82.0 kW

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000023 - Distribution boards


CLASS EC000484 - Energy distributor for construction site

Rated current	125 A	**Leakage current type**	Other	**Degree of protection (IP)**	IP65
Width	870 mm	**Height**	720 mm	**Depth**	375 mm
Model	Distributor cabinet	**Housing material**	Plastic	**Number of socket outlets with protective contact CEE 7/3 (type F)**	0
Number of socket outlets Swiss standard type 13	0	**Number of socket outlets Swiss standard type 15**	0	**Number of socket outlets Swiss standard type 23**	0
Number of socket outlets Swiss standard type 25	0	**Number of miniature circuit breakers (MCB)**	1	**Rated voltage**	400 V
Connected load	82 kW	**Number of CEE socket outlets (IEC 60309) 16 A / 24 V / 2P (L, N)**	0	**Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 3P (L, N, PE)**	2
Number of CEE socket outlets (IEC 60309) 16 A / 230 V / 5P (1, 2, 3, N, PE)	0	**Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 4P (1, 2, 3, PE)**	1	**Number of CEE socket outlets (IEC 60309) 16 A / 400 V / 5P (1, 2, 3, N, PE)**	0
Number of CEE socket outlets (IEC 60309) 32 A / 230 V / 4P (1, 2, 3, PE)	0	**Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 4P (1, 2, 3, PE)**	0	**Number of CEE socket outlets (IEC 60309) 32 A / 400 V / 5P (1, 2, 3, N, PE)**	3
Number of CEE socket outlets (IEC 60309) 63 A / 230 V / 4P (1, 2, 3, PE)	0	**Number of CEE socket outlets (IEC 60309) 63 A / 400 V / 5P (1, 2, 3, N, PE)**	0	**Number of CEE socket outlets (IEC 60309) 125 A / 230 V / 4P (1, 2, 3, PE)**	0
Number of CEE socket outlets (IEC 60309) 125A / 400 V / 5P (1, 2, 3, N, PE)	0	**Number of meter panels**	0	**Main switch**	Power-cut-out switch
Main switch rated current	125 A	**Number of poles main switch**	4	**Number of earth leakage switches 10 mA**	0
Number of earth leakage switches 30 mA	2	**Number of earth leakage switches 100 mA**	0	**Number of earth leakage switches 300 mA**	0
Emergency stop button	Yes	**Suitable according to IEC/EN 61439-4**	Yes		

Technical Characteristics


Differential device	4P 2x63A	**Prese_16A_2P+T**	2	**Prese_32A_2P+T**	-
Prese_16A_3P+N+T	-	**Prese_16A_3P+T**	1	**Schuko/bivalent sockets**	-
shuko bivalent 16A 2P+E	-	**prese_32A_3P+T**	-	**Prese_32A_3P+N+T**	3
Prese_63A_3P+N+T	-	**Prese_63A_3P+T**	-		

Documentation available for download



Instruction booklet

GUIDA DI RIFERIMENTO QUADRI DA CANTIERE TIPO 69008.pdf



Single-line diagram

6910808.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8032793872160

Unit

1 NR

1.025x0.395x0.74 [m]

34 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.