elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC69251

PANEL-MOUNT INCLINED SOCKET IP44 220/240V 3P+N+E 16A

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip44 - 16 a

Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II

Norms

EN 60309-1 EN 60309-2

Description

EN 60309 industrial flush-mount socket. IP44 protection rating. 20° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).
3P+N+E 16A 208-250V~ 9h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)

Number of poles	5	**Degree of protection (IP)**	IP44	**Material**	Plastic
RAL-number	5017	**IEC-amperage**	16 A	**Voltage according to EN 60309-2**	230 V (50+60 Hz) blue
Clock hour position	9 h	**Identification colour**	Blue	**Connection system**	Screwed terminal
Insert direction	Straight	**Surface coating contacts**	Untreated	**Military model**	No
Rated voltage	208 ÷ 250 V	**Rated frequency**	50 ÷ 60 Hz	**Flange size vertical**	85 mm
Drill hole distance vertical	60 mm	**Flange size horizontal**	75 mm	**Drill hole distance horizontal**	60 mm

Documentation available for download



Certification

IMQ_CA02.05863_2025_16A.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8033576770765
Unit
1 NR
0.1633 [kg]



8057711591213
Pack
10 NR
0.185x0.29x0.135 [m]
1.633 [kg]



8033576771861
Cardboard
60 NR
9.798 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.