elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC692721

WALL-MOUNT INCLINED BOX PLUG IP44 220V 2P+E 32A

Industrial > Plugs and sockets > Panel and wall-mount > Wall plugs > Cee appliance inlet (iec 60309) > Ip44 - 32 a

Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II | MADE IN EU

Norms

EN 60309-1 EN 60309-2

Description

Industrial wall plug, type EN 60309. IP44 protection rating. Angled 15°. Base dimensions 71x85mm. Mounting spacing 58x13+33mm. Enclosure with M25 threaded inlet, end cap included. Pre-screwed screw terminals oriented in the same direction for quick wiring. Seal included.
2P+E 32A 200-250V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001319 - CEE appliance inlet (IEC 60309)

Number of poles	3	**Degree of protection (IP)**	IP44	**Material**	Plastic
RAL-number	7035	**IEC-amperage**	32 A	**Voltage according to EN 60309-2**	230 V (50+60 Hz) blue
Clock hour position	6 h	**Identification colour**	Blue	**Phase inverter**	No
Connection system	Screwed terminal	**Insert direction**	Straight	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Construction type**	Surface mounted device plug
Rated voltage	200 ÷ 250 V	**Rated frequency**	50 ÷ 60 Hz		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8054382042419
Unit
1 NR
0.2262 [kg]



8059307218092
Pack
10 NR
2.262 [kg]



8032636767080
Cardboard
40 NR
9.048 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.