

EC692931F

WALL-MOUNT HORIZ. INTERLOCKED SOCKET WITH FUSE HOLDER IP44 220V 3P+E 32A

Industrial > Plugs and sockets > Switched interlocked > Horizontal - with fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip44 - wall-mount

Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II | MADE IN ITALY

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

nterlocked switched surface-mounting socket with fuse base. Protection rating IP44. LED blown fuse indicator. gG type fuses 10.3x38 mm (not included). Dimensions: 196x146x77 mm. 20° inclined socket. Switch type AC23A - 10 kA. Ergonomic handle padlockable in ON/OFF position. Stainless steel cover springs.
3P+E 32A 200-250V~ 9h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	4	**Degree of protection (IP)**	IP44	**Model**	Base unit and cover
Housing material	Plastic	**IEC-amperage**	32 A	**Voltage according to EN 60309-2**	230 V (50+60 Hz) blue
Clock hour position	9 h	**Identification colour**	Blue	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Protection**	Cylindrical fuse
Switch	Mechanical locking	**With earth leakage switch**	No	**Empty locations on mounting rail**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

IMQ_CA02.05695_2025_32A_IOCBF.pdf

Barcode

8033954871831

Unit

1 NR

0.2x0.154x0.145 [m]

0.858 [kg]

8059307218467

Cardboard

10 NR

0.605x0.4x0.35 [m]

8.58 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.