

# EC69351

## PANEL-MOUNT INCLINED SOCKET IP67 380/415V 3P+N+E 63A

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip67 - 63 a

### Technical Symbols/Marks/Approvals

IP67 | IK08 | HF | CE | RoHS II | MADE IN EU

### Norms

EN 60309-1 EN 60309-2

## Description

EN 60309 industrial flush-mount socket. IP67 protection rating. 15° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).
3P+N+E 63A 346-415V~ 6h

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)

| | | | | | |
|---|---|---|---|---|---|
| **Number of poles** | 5 | **Degree of protection (IP)** | IP67 | **Material** | Plastic |
| **RAL-number** | 3000 | **IEC-amperage** | 63 A | **Voltage according to EN 60309-2** | 400 V (50+60 Hz) red |
| **Clock hour position** | 6 h | **Identification colour** | Red | **Connection system** | Screwed terminal |
| **Insert direction** | Straight | **Surface coating contacts** | Untreated | **Military model** | No |
| **Rated voltage** | 346 ÷ 415 V | **Rated frequency** | 50 ÷ 60 Hz | **Flange size vertical** | 112 mm |
| **Drill hole distance vertical** | 88 mm | **Flange size horizontal** | 100 mm | **Drill hole distance horizontal** | 80 mm |

## Documentation available for download



Certification

IMQ_CA02.05861_2025_63A.pdf



Certification

IMQ_CA02.05862_2025_125A.pdf



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8033576770925

**Unit**

1 NR

0.6555 [kg]



8033576778303

**Pack**

2 NR

0.185x0.285x0.135 [m]

1.311 [kg]



8033576771373

**Cardboard**

16 NR

10.488 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.