elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC69401

PANEL-MOUNT STRAIGHT SOCKET IP44 24V 3P 16A

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip44 - 16 a

Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II

Norms

EN 60309-1 EN 60309-2

Description

Industrial flush-mounted socket, type EN 60309. IP44 protection rating. Straight. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).
3P 16A 20-25V~

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)

Number of poles	3	**Degree of protection (IP)**	IP44	**Material**	Plastic
RAL-number	4005	**IEC-amperage**	16 A	**Voltage according to EN 60309-2**	20-25 V (50+60 Hz) violet
Identification colour	Purple	**Connection system**	Screwed terminal	**Insert direction**	Straight
Surface coating contacts	Untreated	**Military model**	No	**Rated voltage**	20 ÷ 25 V
Rated frequency	50 ÷ 60 Hz	**Flange size vertical**	85 mm	**Drill hole distance vertical**	60 mm
Flange size horizontal	75 mm	**Drill hole distance horizontal**	60 mm		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8033954871268

Unit

1 NR

0.1797 [kg]



8057711591251

Pack

10 NR

0.19x0.285x0.135 [m]

1.797 [kg]



8032793873204

Cardboard

80 NR

14.376 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.