

# EC694924F

## PANEL-MOUNT SOCKET WITH FUSE HOLDER SELV 24V 150VA 2P 16A

Industrial > Plugs and sockets > Switched interlocked > Vertical - low voltage > Cee socket outlet, disconnectable (iec 60309) > Flush-mount

### Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II | MADE IN ITALY

### Norms

EN 60309-1 EN 60309-2 EN 60309-4

## Description

Flush-mounted fixed socket with safety transformer 220-24V~ 150 VA. IP44 protection rating. Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. Straight socket. With voltage presence indicator light. With primary+secondary fuse base type gG 10.3x38 mm (fuses not included). LED indicator for blown fuse on the primary circuit. Stainless steel cover closing springs.
2P 16A 24V~ 150VA

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

| | | | | | |
|---|---|---|---|---|---|
| **Number of poles** | 2 | **Degree of protection (IP)** | IP44 | **Model** | Top cover |
| **Housing material** | Plastic | **IEC-amperage** | 16 A | **Voltage according to EN 60309-2** | 20-25 V (50+60 Hz) violet |
| **Identification colour** | Purple | **Contact material** | CuZn | **Surface coating contacts** | Untreated |
| **Military model** | No | **Protection** | Cylindrical fuse | **Switch** | Without on/off switch |
| **With earth leakage switch** | No | **Empty locations on mounting rail** | No | | |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8033954872333

**Unit**

1 NR

0.295x0.12x0.15 [m]

2.02 [kg]

8059307219136

**Cardboard**

10 NR

0.605x0.4x0.35 [m]

20.2 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.