

EC6992330LM

MOBILE CABLE REEL 2X2P+E+2X3P+E - 5X2,5 - IP65 - 50 m

Industrial > Cable reels and extension cords > Cable reels and extension cords >
Cable reel > Cable reel > 4 sockets with wheels - 50 meters cable h07rn-f



Technical Symbols/Marks/Approvals

IP55	GWT 650°	CE	RoHS II		MADE IN ITALY
------	-------------	----	---------	---	---------------------

Norms

EN 61242 EN 61316

Description

Cable reel with galvanized and painted metal support with wheels. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum with automatic braking system and anti-tear cable clamp. Resettable thermal cutout >55 °C. Manual rewind handle. Drum diameter 400 mm. Dimensions 360x410x800 mm.
2 CEE 16A 2P+E 220V~ IP67 sockets
2 CEE 16A 3P+E 380V~ IP67 sockets
H07RN-F cable - 5G2.5 - 50 m
CEE 16A 3P+N+E 380V~ IP67 plug

Etim

GROUP EG020002 - Accessories for power tools

CLASS EC000191 - Cable reel

Degree of protection (IP)	IP55	Colour	Grey	Type of fastening	None
Housing material	Plastic	Number of cores	5	Cable assembly	H07RN-F
Core cross section	2.5 mm²	Number of CEE socket outlets (IEC 60309)	4	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets British Standard BS 1363	0	Number of socket outlets British standard	0	Number of socket outlets Italian standard type P11	0
Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0	Number of universal multi standard sockets	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE	Cable length	50 m
With mounting frame	Yes	Automatic cable winding	No	With thermal overload protection	Yes
With locking	No	With lamp	No	With charging cable for E-Mobility	No
Earthing cable reel	No	Protection	Overcurrent switch		

Technical Characteristics

Power cable coiled	4 kW	Power cable unwound	11.0 kW	Prese_16A_2P+T	2
Prese_16A_3P+N+T	-	Prese_16A_3P+T	2	Schuko/bivalent sockets	-
EN 60309 16A plug	3P+N+T				

Barcode



8033954870216

Unit

1 NR

0.475x0.375x0.81 [m]

20 [kg]