

**EC699P15**

**INDUSTRIAL EXTENSION 16A  
SOCKET-PLUG IP44 3P+N+E 20 m**



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Industrial > Cable reels and extension cords > Cable reels and extension cords > Extension cords > Power cord > 16 a - ip44

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2

**Etim**

**GROUP EG000053 - Batteries, chargers and power cords**

**CLASS EC001576 - Power cord**

<b>Degree of protection (IP)</b>	IP44	<b>Length</b>	20 m	<b>Material outer sheath</b>	Rubber
<b>Colour outer sheath</b>	Black	<b>Reaction-to-fire according to EN 13501-6: Class</b>	Eca	<b>Reaction-to-fire according to EN 13501-6: Smoke production</b>	None
<b>Reaction-to-fire according to EN 13501-6: Flaming droplets/particles</b>	None	<b>Reaction-to-fire according to EN 13501-6: Acidity</b>	None	<b>Outer diameter approximate</b>	17 mm
<b>Nominal voltage</b>	346-415 V	<b>Frequency</b>	50-60 Hz	<b>Number of cores</b>	5
<b>Nominal cross section conductor</b>	2.5 mm <sup>2</sup>	<b>Nominal current</b>	16 A	<b>Temperature resistance</b>	-25-60 °C
<b>With protective conductor</b>	Yes	<b>Oil resistant according to EN IEC 60811-404</b>	Yes	<b>Connection 1</b>	CEE plug (IEC 60309)
<b>Cable entry connection 1</b>	Straight	<b>Connection 2</b>	CEE coupling (IEC 60309)	<b>Cable entry connection 2</b>	Straight
<b>System-oriented connector system</b>	No	<b>Spiralized cable</b>	No	<b>With cord switch</b>	No

**Technical Characteristics**

**Power cable unwound** 11.0 kW

## Barcode



8033954873408

**Unit**

1 NR

0.39x0.295x0.15 [m]

4.3 [kg]