elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**



# EC70020CR

## JOINT PIPE-BOX IP67 Ø20 mm - RED RAL3000 - EASYSYSTEM

Enclosures > Special application systems > Emergency line > Conduits and fittings > Coupler conduit - box

### Technical Symbols/Marks/Approvals

IP67 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

### Norms

EN 61386-1 EN 61386-21

## Description

Conduit-to-box connector made of impact-resistant rigid PVC-based technopolymer. Soft internal sealing ring for conduit tolerance compensation. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread. Supplied with gasket and fixing locknut mounted. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 20 mm - Length 44 mm - Thread length 15 mm

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002326 - Cable plug for cable-/installation tube entry

| | | | | | |
|---|---|---|---|---|---|
| **Suitable for cable diameter** | 20 ÷ 20 mm | **Suitable for built-in installation box** | No | **Suitable for junction box** | Yes |
| **Suitable for cable box** | Yes | **Suitable for expansion ring** | No | **For tube diameter** | 20 mm |
| **Number of conduit lead-ins** | 1 | | | | |

## Technical Characteristics

| | | | |
|---|---|---|---|
| **length** | 44 mm | **thread length** | 15 mm |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8056351663953

**Pack**

25 NR

0.45 [kg]

8056351663717

**Cardboard**

500 NR

0.295x0.39x0.3 [m]

9 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.